



# G2 Wireless Payment Device



- Compact and elegant design.
- Stable communication, long standby time.
- PCI 5.X, UPTS 2.0, EMV, PBOC, PayPass, PayWave approved, payment security guaranteed.



## NEXGO G2 WIRELESS PAYMENT DEVICE



<b>Operating System</b>	Linux
<b>Processor</b>	32-bit ARM9 CPU, 400MHz
<b>Memory</b>	128MB FLASH+64MB RAM
<b>Display</b>	2.4 Inch TFT Colorful Screen, 320 x 240 Pixels
<b>Keypad</b>	10 Numeric Keys, 9 Function Keys, Water-proof and Dust-proof PIN Pad
<b>Touch Screen (Optional)</b>	Touch Screen, E-signature Supported
<b>Printer</b>	High-speed Thermal Printer, Paper Roll Width: 58mm, Paper Roll Diameter: 40mm
<b>Card Readers</b>	Magnetic Card Reader: Track 1/2/3 Bi-directional Smart Card Reader: EMV, PBOC Approved Contactless Card Reader: 13.56MHz, ISO14443, Type A/B, MIFARE. EMV, QPBOC Approved
<b>Peripheral Ports</b>	1 12PIN Pad Interface (1 RS232 Interface, 1 Standard USB-Host Interface) 1 Micro-USB      1 SIM
<b>Connectivity</b>	Basic: GPRS Optional: WCDMA / Wi-Fi / Blue-tooth
<b>PIN Pad</b>	Built-in PIN Pad
<b>Camera(Optional)</b>	0.3 Megapixels, Auto Focus, Supports Barcode And QR Code Reader
<b>Audio</b>	Buzzer
<b>Power</b>	Removable Battery, 3.7V, 2600mAh
<b>Voltage</b>	Input: 100~240V 50~60Hz 0.3A Output: 5V/1A
<b>Physical</b>	165mm L x 78mm W x 56 mm H
<b>Weight</b>	340g (Including Battery)
<b>Environment</b>	Operating Temperature : 0°C to 50°C Storage Temperature : -20°C to 60°C Relative Humidity : 5% to 95%(Non-Condensing)
<b>MTTF</b>	> 50000 Hours
<b>Security</b>	PCI 5.X Approved

